Trade name : Revision date : Print date : UNI301 08.11.2024 08.11.2024

Version (Revision) :

2.0.1 (1.0.1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier UNI301

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Metal working fluids Lubrication at high energy conditions in metal working operations **Uses advised against**

No information available.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor) CNCmarket.ca Inc.

Street: 2360 Portland Street SE

Postal code/City: Calgary, AB, T2G5S2

Telephone : <u>+1 825 454 66 97</u>

E-mail address : info@CNCmarket.ca

1.4 Emergency telephone number Chamtrac: 1-800-424-9200 (24b/

Chemtrec: 1-800-424-9300 (24h/7d)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification selon RPD (DORS/2015-17)

Skin Irrit. 2 ; H315 - Corrosion cutanée/irritation cutanée : Catégorie 2 ; Provoque une irritation cutanée. Eye Irrit. 2 ; H319 - Lésions oculaires graves/irritation oculaire : Catégorie 2 ; Provoque une sévère irritation des yeux. Skin Sens. 1 ; H317 - Sensibilisation cutanée : Catégorie 1 ; Peut provoquer une allergie cutanée.

2.2 Label elements

Labelling according to HPR (SOR/2015-17)

Hazard pictograms



Exclamation mark (GHS07) Signal word

Warning

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
Precautiona	ry statements
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Page : 1 / 12

Trade name :	UNI301		
Revision date :	08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of water/
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents and container in accordance with all local and national regulations.

2.3 Other hazards

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description	
Base Oil and Additives	
Hazardous ingredients	
2-AMINOETHANOL ; CAS No. : 141-43	3-5
Weight fraction :	≥ 1 - < 3 %
Classification:	Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 STOT SE 3 ; H335 Aquatic Chronic 3 ; H412
1-phenoxypropan-2-ol; CAS No.: 770)-35-4
Weight fraction :	≥ 1 - < 5 %
Classification:	Eye Irrit. 2 ; H319
DICYCLOHEXYLAMINE ; CAS No. : 10	1-83-7
Weight fraction :	< 1 %
Classification:	Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410
2-N-BUTYL-BENZO[D]ISOTHIAZOL-3-	ONE ; EC No. : 420-590-7; CAS No. : 4299-07-4
Weight fraction :	≥ 0,1 - < 0,25 %
Classification :	Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410
Further ingredients	

TRIETHANOLAMIN ; CAS No. : 102-71-6

Weight fraction : 1 - 5 %

The highly refined mineral oil contains less than 3% (w/w) DMSO-extract, according to IP 346 and is not considered to be carcinogenic.

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Remove victim out of the danger area. Remove casualty to fresh air and keep warm and at rest. Where appropriate artificial ventilation. In case of respiratory tract irritation, consult a physician.

Page : 2 / 12

Trade name :	UNI301		
Revision date :	08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

Following ingestion

Call a physician immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps.

- **4.2 Most important symptoms and effects, both acute and delayed** No information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide (CO2), Water spray jet, Water mist

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, Nitrogen oxides (NOx), Phosphorus oxides, Smoke and other incomplete combustion products.

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove persons to safety. Avoid contact with skin, eyes and clothes. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Special danger of slipping by leaking/spilling product. Remove all sources of ignition.

6.2 Environmental precautions

Cover drains. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Cover drains. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Trade name :	UNI301		
Revision date :	08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Ventilate affected area. Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Wear personal protection equipment (refer to section 8). Use only in well-ventilated areas. Handle and open container with care. Always close containers tightly after the removal of product. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking.

Protective measures

Measures to prevent fire

Only use the material in places where open light, fire and other flammable sources can be kept away.

Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Shafts and sewers must be protected from entry of the product.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any productimpregnated cleaning rags into your trouser pockets. Use protective skin cream before handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Packaging materials

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect containers against damage. Floors should be impervious, resistant to liquids and easy to clean.

Hints on joint storage

Keep away from: Oxidizing agent

Do not store together with

Food and feedingstuffs

Further information on storage conditions

Recommended storage temperature : 5 - 40°C / 40 - 105°F. **Protect against :** Heat. UV-radiation/sunlight Frost

Storage stability : Product may be stored for up to 12 months under described conditions.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

Base Oil	Alberta Provincial (Canada). OEL: 10 mg/m ³ 15 minutes. Form: Mist OEL: 5 mg/m ³ 8 hours . Form: Mist
	Québec Provincial (Canada). STEV: 10 mg/m ³ 15 minutes. Form: mist TWAEV: 5 mg/m ³ 8 hours. Form: mist

Trade name :	UNI301		
Revision date :	08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

2-AMINOETHANOL ; CAS No. : 141-43-5	Alberta Provincial (Canada). OEL: 6 ppm 15 minutes OEL: 3 ppm 8 hours
	British Columbia Provincial (Canada). TWA: 3 ppm 8 hours STEL: 6 ppm 15 minutes
	Ontario Provincial (Canada). TWA: 3 ppm 8 hours STEL: 6 ppm 15 min
	Québec Provincial (Canada). TWA: 3 ppm 8 hours STEL: 6 ppm 15 min
	Saskatchewan Provincial (Canada). TWA: 3 ppm 8 hours STEL: 6 ppm 15 minutes
Triethanolamine; CAS No. : 102-71-6	Alberta Provincial (Canada). OEL: 5 mg/m ³ 8 hours
	British Columbia Provincial (Canada). TWA: 5 mg/m ³ 8 hours
	Ontario Provincial (Canada). TWA: 3.1 mg/m ³ 8 hours TWA: 0.5 ppm 8 hours
	Québec Provincial (Canada). TWAEV: 5 mg/m ³ 8 hours
	Saskatchewan Provincial (Canada). STEL: 10 mg/m ³ 15 minutes TWA: 5 mg/m ³ 8 hours

NOTE: Limits/standards shown for guidance only. Follow applicable regulations

8.2 Exposure controls

Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Eye/face protection

Eye glasses with side protection EN 166

Skin protection

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Tested protective gloves must be worn: DIN EN 374 Do not wear gloves near rotary machines and tools.

Suitable material :

Wearing time with permanent contact:

- Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber), Thickness of the glove material: 0,70 mm
- Breakthrough time (maximum wearing time): > 480 min

Wearing time with occasional contact (splashes):

Page : 5 / 12

(EN/CDN)

Trade name :	UNI301		
Revision date :	08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber), Thickness of the glove material: 0,40 mm Breakthrough time (maximum wearing time): > 30 min

breaktinough time (maximum wearing time). > 50 m

Unsuitable material : PVA (Polyvinyl alcohol),

Breakthrough time (maximum wearing time): : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Check leak tightness/impermeability prior to use.

Body protection

If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Respiratory protection

Usually no personal respirative protection necessary. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist formation.

General information

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any productimpregnated cleaning rags into your trouser pockets. Wash contaminated clothing prior to re-use. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state :	Liquid					
Colour :	light yellow	1				
Odour :	characteris	tic				
Safety character	istics					
Melting point/freezing	g point :			No data available		
Initial boiling point an range :	d boiling	(1013 hPa)	>	100	°C	
Flammability:				flammable		
Lower explosion limit	:			No data available		
Upper explosion limit	:			No data available		
Flash point :			>	100	°C	DIN EN ISO 2592
Auto-ignition tempera	ture :			No data available		
Decomposition tempe	rature :			not determined		
рН :		(20 °C / 5 Weight-%)		9,9		DIN 51369
Cinematic viscosity :		(20 °C)	approx.	115	mm²/s	DIN EN ISO 3104
Water solubility :		(20 °C)		miscible		
log P O/W :				not applicable		
Vapour pressure :		(20 °C)		No data available		
Density :		(15 °C)		0,987	g/cm ³	DIN EN ISO 12185
Relative vapour densit	ty:	(20 °C)		No data available		
Maximum VOC conten (Switzerland) :	t			0	Weight-%	
Other information	า					

None

9.2

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Trade name :	UNI301		
Revision date :	08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions No known hazardous reactions.

- **10.4 Conditions to avoid** No information available.
- **10.5 Incompatible materials** Oxidising agent, strong.

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1 Information on hazard classes

Toxicological data are not available. The statement is derived from the properties of the single components.

Acute toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

Acute oral toxicity	
Parameter :	LD50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Exposure route :	Oral
Species :	Rat
Effective dose :	1000 mg/kg
Parameter :	LD50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (DICYCLOHEXYLAMINE; CAS No.: 101-83-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	200 mg/kg
Acute dermal toxicity	
Parameter :	LD50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	1025 mg/kg
Method :	literature
Parameter :	LD50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (DICYCLOHEXYLAMINE; CAS No.: 101-83-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	200 - 316 mg/kg
Acute inhalation toxicity	
Parameter :	LC50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Exposure route :	Inhalation (dust/mist)
Species :	Rat
Effective dose :	> 5,4 mg/l
Corrosion	
Irritating to eyes and skin.	
Skin corrosion/irritation	
Parameter :	Skin corrosion/irritation (2-AMINOETHANOL ; CAS No. : 141-43-5)

Page : 7 / 12

ade name : evision date : int date :	UNI301 08.11.2024 08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Species :		Rabbit	
Result :		corrosive	
Method :		OECD 404	
Parameter :		Skin corrosion/irritation (1-phenoxypropan-2-ol; CAS No.: 770-35-4)	
Species :		Rabbit	
Result :		Slightly irritant but not relevant for classification	
Parameter :		Skin corrosion/irritation (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7))
Species :		Rabbit	
Result :		corrosive	
Serious eye da	mage/eye irritat	tion	
Parameter :		Serious eye damage/eye irritation (2-AMINOETHANOL ; CAS No. : 141	43-5)
Species :		Rabbit	
Result :		corrosive	
Method :		OECD 405	
Parameter :		Serious eye damage/eye irritation (1-phenoxypropan-2-ol ; CAS No. :	770-35-4)
Species :		Rabbit	
Result :		irritating	
Parameter :		Serious eye damage/eye irritation (DICYCLOHEXYLAMINE ; CAS No. :	101-83-7)
Species :		Rabbit	
Result :		corrosive	
Respiratory of the second s	or skin sensit	isation	
May cause sensit	tization by skin cor	ntact.	
Skin sensitisat	ion		
Parameter :		Skin sensitisation (1-phenoxypropan-2-ol; CAS No.: 770-35-4)	
Species :		Guinea pig	
Result :		Not sensitising.	
CMR effects	(carcinogenie	city, mutagenicity and toxicity for reproduction)	
Carcinogenicit	y _		
Based on availa	ble data, the class	ification criteria are not met.	
Germ cell muta	agenicity		
		ification criteria are not met.	
Reproductive t			
-	-	ification criteria are not met.	
STOT-single			
STOT SE 1 and	•		
0.0.01000	-	ification criteria are not met	
		ification criteria are not met.	
STOT-repeat	-		
STOT RE 1 and			
Based on availa		ification criteria are not met.	
	azard		
Aspiration ha			
•		ication criteria are not met. For viscosity data, see section 9.	
•	ole data, the classif	, ,	

SECTION 12: Ecological information

12.1 Toxicity

For the product ecotoxicological data are not available. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Aquatic toxicity

Harmful to aquatic life.

Trade name : Revision date : Print date :	UNI301 08.11.2024 08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Acute (short-to	erm) fish toxicity	,	
Parameter :	arameter : LC50 (2-AMINOETHANOL ; CAS No. : 141-43-5)		
Species : Cyprinus carpio (Com		Cyprinus carpio (Common Carp)	
Effective dose	:	> 100 mg/l	

Lifective dose.	> 100 mg/i
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species :	Pimephales promelas (fathead minnow)
Effective dose :	> 100 mg/l
Method :	OECD 203
Parameter :	LC50 (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Species :	Leuciscus idus (golden orfe)
Effective dose :	12 mg/l
Exposure time :	96 h
Method :	OECD 203
Acute (short-term) toxicity to cr	rustacea
Parameter :	EC50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Species :	Daphnia magna (Big water flea)
Effective dose :	65 mg/l
Exposure time :	48 h
Parameter :	EC50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species :	Daphnia magna (Big water flea)
Effective dose :	> 370 mg/l
Method :	OECD 202
Parameter :	EC50 (DICYCLOHEXYLAMINE; CAS No.: 101-83-7)
Species :	Daphnia magna (Big water flea)
Effective dose :	8 mg/l
Exposure time :	48 h
Method :	OECD 202
Acute (short-term) toxicity to al	
Parameter :	EC50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Species :	Scenedesmus subspicatus
Effective dose :	22 mg/l
Exposure time :	72 h
Parameter :	EC50 (1-phenoxypropan-2-ol; CAS No.: 770-35-4)
Species :	Desmodesmus subspicatus
Effective dose :	> 100 mg/l
Parameter :	EC50 (DICYCLOHEXYLAMINE; CAS No.: 101-83-7)
Species :	Scenedesmus subspicatus
Effective dose :	3,3 mg/l
Exposure time :	72 h
Method :	OECD 201
awalahawaa awalalawa dahili	A

12.2 Persistence and degradability

Abiotic degradation

Poorly eliminated from water.

Biodegradation

Part of the components is biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

- No information available.
- 12.5 Results of PBT and vPvB assessment

Trade name :	UNI301		
Revision date :	08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Consult the appropriate local waste disposal expert about waste disposal. Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Do not pressurise, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group No dangerous good in sense of these transport regulations.

14.5 Environmental hazards No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Canada

NFPA Hazard ID: Health: 2; Flammability: 1; Reactivity: 1 **HMIS Hazard ID:** Health: 2; Flammability: 1; Reactivity: 1

CEPA: All components of this product are either on the Domestic Substance List (DSL) or are exempt.

This material is considered to be hazardous according to regulatory guidelines.

This product has been classified in accordance with hazard criteria of the Hazardous Products Regulations (HPR) SOR/2015-17 and the SDS contains all the information required by the HPR SOR/2015-17.

15.2 Chemical Safety Assessment

No information available.

Trade name : Revision date : Print date : UNI301 08.11.2024 08.11.2024

Version (Revision) :

2.0.1 (1.0.1)

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements ·

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) CAS: Chemical Abstracts Service (division of the American Chemical Society) GHS: Globally Harmonized System on the Classification and Labelling of Chemicals CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures, LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent EC50: Effective concentration, 50 percent DNEL: Derived No Effect Level PNEC: Predicted No Effect Concentration PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

Sources of information used in preparing this SDS included one or more of the following: Product Dossiers and SDS from suppliers, complemented by public sources, as appropriate (GESTIS, the EU IUCLID Data Base, U.S. NTP publications, e.g.).

16.4 Classification for mixtures and used evaluation method

No information available.

16.5 Relevant H-phrases (Number and full text)

H301 Toxic if swallowed. Harmful if swallowed. H302 H311 Toxic in contact with skin. Harmful in contact with skin. H312 H314 Causes severe skin burns and eye damage. May cause an allergic skin reaction. H317 H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

16.6 Training advice

Provide adequate information, instruction and training for operators.

16.7 Additional information

None

Trade name : Revision date :	UNI301 08.11.2024	Version (Revision) :	2.0.1 (1.0.1)
Print date :	08.11.2024		

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.